Technical Data Sheet/Publication Date: 01.01.2013/Revision No: 01/Revision Date:20.11.2017

GYPSUM BOARD SCREW-ANCHOR

DESCRIPTION

-Screws; used in the construction of gypsum board partition walls, wall lining systems and suspended ceiling systems, to fix gypsum boards to galvanized profiles.
-Anchors; used in all interior wall and suspended ceiling applications made with gypsum board. Used to fix the system to the ceiling and wall in gypsum board partition wall, wall lining, shaft wall and suspended ceiling applications.

FEATURES

Screws;
-Made of carbon steel and passes the 48-hour salt water test.
-Coated with black phosphate for protection against corrosion.
-Self-drills its own hole and thread in galvanized steel sheet profiles.
Anchors;
-Used for safe application.
-Has high pull-out strength.
-Does not loosen at the fixing point.

APPLICATION

-Bugle-Head Screw; used in all interior wall and suspended ceiling applications made with gypsum board. Used to fix gypsum board to galvanized profiles thinner than 0.88 mm.
-Drill-Tip Screw; used in all interior wall and suspended ceiling applications made with gypsum board. Used to fix gypsum board to galvanized profiles or metal construction thinner than 2.20 mm.
-Wafer-Head Screw; used in all interior wall and suspended ceiling applications made with gypsum board. Generally used together with an 8 mm plastic anchor to fix the system to the ceiling and wall in partition wall, wall lining, shaft wall and suspended ceiling applications.
-Plastic Anchor; used in all interior wall and suspended ceiling applications made with gypsum board. Generally consists of an 8 mm plastic anchor together with a 45 mm wafer-head screw. Used to fix the system to the ceiling and wall in gypsum board partition wall, wall lining, shaft wall and suspended ceiling applications.
-Steel Anchor; used in interior suspended ceiling applications to fix the metal load-bearing frame to the ceiling.

TECHNICAL SPECIFICATIONS

	Bugle-Head Screw					Drill-Tip Screw				Wafer-Head Screw
Screw Length mm	25	38	45	55	70	25	35	45	55	45
Unit Weight (g/pc)	1.4	2	2.4	2.9	4.3	1.6	2.1	2.5	2.8	3.7
Diameter mm	3.5				4.2	3.5				4.8
Head diameter mm	8									11
Coating type	Black Phosphate									Metallic

	Plastic Anchor	Steel Anchor
Diameter mm	8	M6
Packaging Box	500 pcs	100 pcs

Technical Data Sheet/Publication Date: 01.01.2013/Revision No: 01/Revision Date:20.11.2017

PACKAGING

	Bugle-Head Screw					Drill-Tip Screw				Wafer-Head Screw
	25	38	45	55	70	25	35	45	55	45
Packaging weight (kg/box)	1.4	2	2.4	2.9	1.3	1.6	2.1	2.5	2.8	1.85
Number of screws per box	1000				300	1000				500